# HOLLACE CLUNY



# THIN MULTIPLES TRIAD

## BY <u>JUNIPER</u>

The THIN Multiples Triad arranges three light segments in a linear trio for brighter illumination while maintaining a slender profile. Magnetic connections into precision-machined solid brass hardware enable the 1/2-inch light segments to fully rotate for direct and indirect lighting solutions.

### Dimensions

Available in multiples of 24" and 36" segments.

#### **Material Options**

Brushed brass, Satin Nickel, Black Oxide, LIGHT QUALITY CRI 95+, R9 90+, LED Bronze LIFE 50,000 hrs, L80, CERTIFICATIONS

#### Lamping

LIGHT QUALITY CRI 95+, R9 90+, LED LIFE 50,000 hrs, L80, CERTIFICATIONS cUL, UL, CE, Damp Location Rated, Title 24, WATTAGE & LUMENS (PER SECTION), 24 IN – 20.4W, 0-1800LM 36 IN – 28.8W, 0-2760LM, WEIGHT 24 IN – 2.7 lbs 36 IN – 3 lbs, MOUNTING 10ft 1/16" aircraft cable, field adjustable 16ft Clear-jacketed 22AWG co-axial silver cord, field adjustable Direct-mounting and center-mounting with Linear Cable Collar options available (for up to 2 connected sections)